

GOODWE

ES Uniq Series

3-12kW | Single Phase | 1/2 MPPTs
Hybrid Inverter (LV)

GoodWe's ES Uniq Series inverter, available in 3-12kW capacities, are specifically designed for residential PV installations. It offers flexible compatibility with both on-grid and off-grid systems and support parallel connection of up to 6 inverters for easy system expansion. The ES Uniq inverters feature a user-friendly touch-screen LCD display for intuitive operation and monitoring, and can be combined with a range of battery capacities and brands, including GoodWe's Lynx A and Lynx U batteries.



Flexible & Adaptable Applications

- 3-in-1 Port: generator & smart loads & on-grid inverter
- Micro-grid operation with PV inverter
- Supports on- and off-grid parallel operation of up to 6 units



Superb Safety & Reliability

- AI-driven AFCI¹
- IP66 ingress protection



Higher Power Generation

- Max. 20A DC input current per string
- 200% PV input oversizing



Smart Control & Monitoring

- Smart load control
- Seamless switching to backup <4ms



1: Optional functions or devices are purchased separately.

Technical Data		GW3000-ES-C10	GW3600-ES-C10	GW5000-ES-C10	GW6000-ES-C10	GW8000-ES-C10	GW10K-ES-C10	GW12K-ES-C10
Battery Input Data								
Battery Type ^{*1}					Li-Ion / Lead-acid			
Nominal Battery Voltage (V)					48			
Battery Voltage Range (V)					40 ~ 60			
Start-up Voltage (V)					44.2			
Number of Battery Input					1			
Max. Continuous Charging Current (A)	70	90	120	140	160	200	240	
Max. Continuous Discharging Current (A)	70	90	120	140	160	200	240	
Max. Charging Power (kW)	3.0 ^{*2}	3.6 ^{*2}	5.0 ^{*2}	6.0 ^{*2}	8.0 ^{*3}	10.0 ^{*3}	12.0 ^{*3}	
Max. Discharging Power (kW)	3.3 ^{*2}	3.96 ^{*2}	5.5 ^{*2}	6.6 ^{*2}	8.8 ^{*3}	11.0 ^{*3}	13.2 ^{*3}	
PV String Input Data								
Max. Input Power (kW)	6.0	7.2	10.0	12.0	16.0	20.0	24.0	
Max. Input Voltage (V) ^{*4}				600				
MPPT Operating Voltage Range (V) ^{*5}				60 ~ 550				
Start-up Voltage (V)				58				
Nominal Input Voltage (V)				360				
Max. Input Current per MPPT (A)	20	20	20	20	32 / 16 ^{*6}	32 / 32 ^{*6}	32 / 32 ^{*6}	
Max. Short Circuit Current per MPPT (A)	26	26	26	26	48 / 24	48 / 48	48 / 48	
Number of MPPT Trackers	1	2	2	2	2	2	2	
Number of Strings per MPPT	1	1	1	1	2 / 1	2 / 2	2 / 2	
AC Output Data (On-grid)								
Nominal Output Power (kW)	3.0	3.6	5.0	6.0	8.0	10.0	12.0	
Nominal Apparent Power Output to Utility Grid (kVA)	3.0	3.6	5.0	6.0	8.0	10.0	12.0	
Max. AC Active Power (kW) ^{*7*}	3.3	3.96	5.5	6.6	8.8	11.0	13.2	
Max. Apparent Power Output to Utility Grid (kVA) ^{*7*}	3.3	3.96	5.5	6.6	8.8	11.0	13.2	
Max. Apparent Power from Utility Grid (kVA)	7.04	7.04	8.8	8.8	16.5	16.5	16.5	
Nominal Output Voltage (V)				220 / 230 / 240				
Output Voltage Range (V)				170 ~ 280				
Nominal AC Grid Frequency (Hz)				50 / 60				
AC Grid Frequency Range (Hz)				45 ~ 55 / 55 ~ 65				
Max. AC Current Output to Utility Grid (A)	15	18	25	30	40	50	60	
Max. AC Current From Utility Grid (A)	32	32	40	40	75	75	75	
Power Factor			~1 (Adjustable from 0.8 leading to 0.8 lagging)					
Max. Total Harmonic Distortion				<3%				
AC Output Data (Back-up)								
Back-up Nominal Apparent Power (kVA)	3.0	3.6	5.0	6.0	8.0	10.0	12.0	
Max. Output Apparent Power without Grid (kVA)	3.3 (6.0, 10s)	3.96 (7.2, 10s)	5.5 (10.0, 10s)	6.6 (12.0, 10s)	8.8 (16.0, 10s)	11.0 (20.0, 10s)	13.2 (24.0, 10s)	
Max. Output Apparent Power with Grid (kVA)	7.04	7.04	8.8	8.8	16.5	16.5	16.5	
Max. Output Current without Grid (A)	15	18	25	30	40	50	60	
Max. Output Current with Grid (A)	32	32	40	40	75	75	75	
Nominal Output Voltage (V)				220 / 230 / 240				
Nominal Output Frequency (Hz)				50 / 60				
Output THDv (@Linear Load)				<3%				
AC Data (Generator)								
Nominal Apparent Power from AC generator (kVA)	3.0	3.6	5.0	6.0	8.0	10.0	12.0	
Max. Apparent Power from AC generator (kVA)	3.3	3.96	5.5	6.6	8.8	11.0	13.2	
Nominal Input Voltage (V)				220 / 230 / 240				
Input Voltage Range (V)				170 ~ 280				
Nominal AC generator Frequency (Hz)				50 / 60				
AC generator Frequency Range (Hz)				45 ~ 55 / 55 ~ 65				
Max. AC Current From AC generator (A)	32.0	32.0	40.0	40.0	50.0	54.5	54.5	
Nominal AC Current From AC generator (A)	13.7 at 220V	16.4 at 220V	22.8 at 220V	27.3 at 220V	36.4 at 220V	45.5 at 220V	54.5 at 220V	
	13.1 at 230V	15.7 at 230V	21.8 at 230V	26.1 at 230V	34.8 at 230V	43.5 at 230V	52.2 at 230V	
	12.5 at 240V	15.0 at 240V	20.9 at 240V	25.0 at 240V	33.3 at 240V	41.7 at 240V	50.0 at 240V	
Nominal Input Current (A)	13.7 at 220V	16.4 at 220V	22.8 at 220V	27.3 at 220V	36.4 at 220V	45.5 at 220V	54.5 at 220V	
	13.1 at 230V	15.7 at 230V	21.8 at 230V	26.1 at 230V	34.8 at 230V	43.5 at 230V	52.2 at 230V	
	12.5 at 240V	15.0 at 240V	20.9 at 240V	25.0 at 240V	33.3 at 240V	41.7 at 240V	50.0 at 240V	
Efficiency								
Max. Efficiency				97.6%				
European Efficiency				96.2%				
Max. Battery to AC Efficiency				95.5%				
MPPT Efficiency				99.9%				
Protection								
PV String Current Monitoring				Integrated				
PV Insulation Resistance Detection				Integrated				
Residual Current Monitoring				Integrated				
PV Reverse Polarity Protection				Integrated				
Anti-islanding Protection				Integrated				
AC Overcurrent Protection				Integrated				
AC Short Circuit Protection				Integrated				
AC Overvoltage Protection				Integrated				
DC Switch				Integrated				
DC Surge Protection				Type III				
AC Surge Protection				Type III				
AFCI				Optional				
Rapid Shutdown				Optional				
Remote Shutdown				Integrated				
General Data								
Operating Temperature Range (°C)				-35 ~ +60				
Relative Humidity				0 ~ 95%				
Max. Operating Altitude (m)				3000				
Cooling Method		Natural Convection				Smart Fan Cooling		
User Interface				LCD, WLAN + APP				
Communication with BMS				CAN				
Communication				RS485, WiFi + LAN + Bluetooth				
Communication Protocols				Modbus-RTU, Modbus-TCP				
Weight (kg)	14.5	15.5	15.5	15.5	27.0	29.0	29.0	
Dimension (W x H x D mm)		560 x 415 x 204			560 x 444.5 x 226			
Topology				Non-isolated				
Ingress Protection Rating				IP66				
Mounting Method				Wall Mounted				

*1: The Li-Ion battery usually contain two mainstream type: LFP and Ternary Lithium battery.

*2: When the PV input voltage is higher than 500V, the battery charging and discharging power will be gradually limited, and the power limitation will be lifted after the input voltage is lowered.

*3: When the PV input voltage is higher than 490V, the battery charging and discharging power will be gradually limited, and the power limitation will be lifted after the input voltage is lowered.

*4: When the PV input voltage is higher than 600V, the inverter will enter standby mode. The inverter will return to the MPPT working voltage range when the voltage returns to the MPPT working voltage range.

*5: The inverter will enter standby mode when the voltage returns to the MPPT working voltage range.

*6: The maximum input current per string is 16A. Or For the MPPT with two strings, the current of each string is 16A.

*7: For Sri Lanka, Max. Output Power (kW) is 3.0kW for GW3000-ES-C10, 3.6kW for GW3600-ES-C10, 5.0kW for GW5000-ES-C10, 6.0kW for GW6000-ES-C10, 8.0kW for GW8000-ES-C10, 10.0kW for GW10K-ES-C10, and 12.0kW for GW12K-ES-C10.

*8: For Brazil and Chile, the max. AC output power is Pn, such as the max. AC output power of GW8000-ES-C10 is 8000W (VA).

*: Please visit GoodWe website for the latest certificates.

